



**6596 New Peachtree Rd.
Doraville, GA 30340
770-303-0878
Fax: 770-455-6531**



**PRODUCT DATA SHEET
SOILOC - WA™**

WATER ADDITIVE FOR DUST SUPPRESSION (PM-10)

1.0 MATERIAL DESCRIPTION:

HERCULES SOILOC-WA is water-soluble wetting agent/surfactant. When mixed with water in trace amounts the water's surface tension is reduced allowing the water droplet to more easily penetrate soil particles. It is environmentally safe, biodegradable, non-flammable, non-corrosive; not harmful to skin, vegetation or wildlife.

2.0 INTENDED USE:

HERCULES SOILOC-WA is intended to be diluted with water & sprayed on Gravel Road, Dirt Roads or Construction Sites to control airborne dust (PM-10).

Some advantages when used in road watering:

The road watering operation is labor & equipment intensive. But, in some circumstances watering is still the best dust control method. HERCULES SOILOC-WA makes the watering operation 50% more efficient saving time & money.



- Improves deep-water penetration even in hard to penetrate surfaces.
- Slows evaporation.
- Reduces water waste due to puddling, run-off & evaporation.
- Lower overall water quantities needed per application.
- Compatible with most other dust control methods

3.0 APPLICATION:

Mix with water prior to use. Apply with standard water trucks / sprayers / hydraulic equipment.

	HERCULES SOILOC-WA	Water	Application Rate
First Application	1 Gal.	1,000 Gal.	*
Subsequent Applications	1 Gal.	3,000 Gal.	*

* Apply until desired moisture content is achieved.

4.0 PACKAGING:

330 gal. totes, 55 gal. steel drums, 55 gal. fiber drums, 5 gal. pails.

5.0 CAUTION:

KEEP OUT OF REACH OF CHILDREN.
HARMFUL IF SWALLOWED!

6.0 STORAGE:

KEEP FROM FREEZING.

7.0 CLEAN-UP:

Because this product is used only in a highly diluted form little or no clean-up is needed after application.